

# Overview of Blockchain Technology: Consensus, Architecture, and Its Future Trends

Madhav Singh Solanki

SOEIT, Sanskriti University, Mathura, Uttar Pradesh, India

Correspondence should be addressed to Madhav Singh; [madhavsolanki.cse@sanskriti.edu.in](mailto:madhavsolanki.cse@sanskriti.edu.in)

Copyright © 2021 Madhav Singh Solanki. This is an open-access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

**ABSTRACT-**The blockchain technology that underpins Bitcoin has lately gained a lot of traction. Blockchain is a decentralized transaction ledger that is immutable. Blockchain applications are emerging in a variety of fields, including financial services, reputation systems, and the Internet of Things (IoT), among others. Nonetheless, concerns with blockchain knowledge, like as security or scalability, have yet to be solved. Bitcoin can only process 7 transactions per second, making it unsuitable for high-frequency trading. Larger blocks, on the other hand, imply more storage capacity and less network transfer. Because fewer individuals desire to own such a large blockchain, this will ultimately lead to centralization. This article provides a comprehensive description of blockchain technology. The researcher first provides an overview of blockchain architecture and then compares many commonly utilized consensus algorithms in different blockchains. A brief summary of technical difficulties and current advances is also included. They also highlight possible future blockchain developments.

**KEYWORDS-** Bitcoin, Block Chain, Consensus, Decentralization, Scalability.

## I. INTRODUCTION

Bitcoin has become a buzzword in both business and academia. One of the most widely used cryptocurrencies is Bitcoin. In 2015, it had a net worth market of \$9 billion, after which it was a great success. The Bitcoin network sends bitcoins by displaying messages that are digitally signed by all parties involved, and the Bitcoin core technology creates databases using a specifically built data storage architecture. All conversations are stored in the block slope, thus blockchain may be regarded a community database. As additional blocks are added to the chain, it continues to grow. Asymmetric encryption and global consensus methods have been implemented for device protection and header compatibility. Decentralization, durability, transparency, and auditability are all important features of blockchain technology. With these

characteristics, blockchain may save money and increase efficiency. Block chain, such as intangible assets, remittances, and electronic payments, may be used for different financial services since payments may be made without the need of a bank or other middleman[1]. Smart contracts, public utilities, information and communication technologies, security systems, and reputation systems are only some of the applications. These are some of the block chain's application areas. There are many features of block chain that set it apart from other kinds of money, including the fact that it is decentralized, meaning that power is dispersed rather than centralized. Every user on the blockchain has the potential to become a payment processor for the network. Furthermore, once a transaction has been recorded on a blockchain, it cannot be changed. Customers will be drawn to businesses that have a high level of trustworthiness and authenticity. Blockchain, on the other hand, is distributed, allowing for the avoidance of a single point of failure[2]. When it comes to intelligent agreements, that once blockchain contract is in place, miners may automatically complete the contract. Larger blocks, on the other hand, imply more storage capacity and less network transfer. As a result, balancing the size of blocks with defense was a tough task. Another issue that was identified was that miners may earn more than their fair share of money by using an arrogant mining technique. Miners are covering their mined blocks ahead of time in order to earn more money. Although this technique is popular, twigs may take up residence, preventing the development of blockchain. As a result, some remedies to this issue must be suggested. In reality, it has been shown that in blockchain applications, data protection leakage occurs exclusively with the public and private keys. In contrast, existing consensus methods, such as function or stake confirmation, have significant flaws. For example, research data consumes too much energy, while evidence of a consensus process shows that the rich are becoming poorer. A lot of literature has been written on block chain, including blogs, wikis, web updates, journal papers, and conference proceedings[3]. On decentralized digital

currencies like Bitcoin, scientists conducted a scientific analysis. The paper, on the other hand, concentrated on digital currencies based on block chain technology. A blockchain technical study was released by Nomura Research Institute[4]. The remaining tabloids are ordered as follows. Part 2 delves further into the blockchain idea. In Section III, we'll look at some of the most popular consensus algorithms utilized in blockchain. Section IV discusses the technical competitors and current advances in this area. Section V discusses future options, while the last section covers the whole block chain technology[5].

### A. The Architecture of the Blockchain

Similar to conventional community records, blockchain is a block sequence or a digital spreadsheet providing complete information about company activities. A hash is generated after each transaction. The hash is determined by both the current and previous transactions. Because the sequence of the transactions is so critical, even a little modification will result in a different hash. Nodes keep a careful eye on the hash, and if there isn't any change, the transaction is approved. The blocks relate to one another, forming a block chain. The parent-less genesis block, which depicts the internal blockchain in full, is the first block of a blockchain[6].

- A block is made up of two parts: a header and a body. The block header, in particular.
- Block type: defines which validation rules should be applied to specific blocks.
- Merkle tree's root hash: the block hash in the chain of all transactions.
- Time stamp: current time in universal time as seconds after January 1st, 1970.
- Nonce: a four-byte region that typically starts at zero and grows with each hash estimate.
- The hash parent block: a 256-bit hash algorithm referring to the final row.

A transfer tracker makes up the network body. The total number of transactions including a component varies depending on the size and complexity of the package. Asymmetric cryptography techniques are used by Blockchain to validate transaction authenticity. The cryptographic signature based on asymmetric encryption is employed in an untrustworthy environment. Following that, we'll have a look at the digital signature.

### B. Signature on a Computer

Every user receives a set of private and public keys. The private key is used to guarantee the security of transactions when they are signed. Digital transactions that have been signed are disseminated throughout the network. The signing stage and the testing stage are the two stages of a typical digital signature. For example, one Alice user may want to send a message to another Alice user[7].

During the signing procedure, Alice encrypts the database using a private key and delivers the authenticated document and information to Bob.

During the authentication procedure, Bob verifies the principles using Alice's public key. As a result, Bob can quickly determine if the data has been damaged. The elliptical curve of the digital signature is the digital signature algorithm used in blockchains (ECDSA).

### C. Characteristics of the Blockchain

In a nutshell, the following are the main features of blockchain:

- a) *Decentralization*: In conventional centralized transaction systems, each transaction must be verified by a central trustworthy agency, resulting in high server costs and performance problems. In contrast to centralized mode, blockchain does not need a third party. Blockchain uses consensus methods to make the decentralized system stable.
- b) *Consistency*: Connections can be readily verified, and sensible miners would refuse to accept fraudulent transactions. In the blockchain, deleting or rolling back transactions is almost impossible. Missing transaction blocks may be found in a matter of seconds.
- c) *Anonymity*: Each user may interact with a blockchain discourse without revealing his or her true identity. It's worth noting that, owing to its inherent limitations, blockchain can't offer complete privacy protection.
- d) *Accountability*: The Bitcoinblockchain stores customer balance data using a Model UTXO, which means that each transaction includes a number of unused transactions that must be indexed. The status of such unspent transactions is changed from incomplete to expendable when they are recorded in the blockchain. As a result, transactions can be readily tracked and verified.

### D. Taxonomy of Blockchain Schemes

Private ledger, public blockchain, and blockchain consortium are the three types of blockchain networks now in use. The growing record is open to the public, and anybody with access to the public blockchain may participate in the consensus process. In a network blockchain, only a set of pre-selected nodes will be utilized, among other things. Only specified nodes from a single organization may participate in the consensus process for private blockchains. A core network is created when a company controls a private blockchainentirely[8,9].

- a) *Consensus Determination*: In a public blockchain, each node may participate in the consensus process. Furthermore, only a few nodes are interested in verifying the consortium blockchain. In terms of the personal chain, it is completely controlled by one organization and the organization.
- b) *Immutability*: Because data is kept on a large number of members, it is almost impossible to abuse transactions in a shared ledger. Transactions inside a

consortium blockchain or private blockchain, on the other hand, may be readily manipulated due to the restricted number of members.

- c) *Efficiency*: Because the public blockchain network includes a large number of nodes, transactions and blocks may be spread out across time. As a result, transaction output is restricted, and latency is significant. With consortium blockchain, there will be fewer validators and the system will be more well-organized.
- d) *Centralized*: The primary distinction between the three kinds is that the public, blockchain, and private blockchains are all decentralized, with the blockchain community acting as a partly centralized layer.
- e) *Consensus Process*: Anyone in the globe may participate in the public blockchain verification phase. Both the private blockchain and the blockchain consortium are acceptable in contrast to public blockchain. Many people and active groups may be drawn to public blockchain since it is accessible to the whole globe. Every day, more public blocks emerge. Day after day, after day. In terms of the blockchain consortium, this may be utilized in a variety of business applications. The consortium's blockchain applications are presently being developed by Hyper ledger. Ethereum also provides tools for creating consortium blockchains.

#### E. Algorithms for Achieving Consensus

As a transformation to the Byzantine general (BG) issue, blockchain demonstrates how to reach consensus among untrusted nodes. In the BG problem, a group of generals controlling a portion of the Byzantine army is circling the city. Those generals would rather assault than retreat. Nonetheless, the assault would fail if just one of the generals attacked the region. As a result, a consensus on whether to assault or withdraw must be established. In a dispersed context, reaching agreement is difficult. Because of the network implementation, bitcoin has an issue. There is no central blockchain node that guarantees dispersed network leaders are all equal. To maintain reliable ledgers, further protocols are needed at different nodes. This article now presents several typical methods to reaching agreement in blockchain[10].

#### F. Consensus-building Techniques

PoW is a consensus solution in the Bitcoin network. In a decentralized network, someone must be chosen to keep track of the transactions. The best method is to pick at random. Random selection, on the other hand, is vulnerable to assaults. It will take a lot of study to show that if a node attempts to create a chain of transactions, it is unlikely to attack the network. A computer is usually used to calculate the function. The hash value of the block header is calculated by that Pow network node. The block header contains a nonce, and minerals alter the nonce to get

various Hash values. The measured value is equal to or higher than a particular quantity, according to consensus.

When a node exceeds the goal value, the block is transmitted to other nodes, and the hash value's validity is shared. Other miners add this new block to their blockchains after the construction is confirmed. Miners are nodes that measure hash values, as well as Bitcoin mining is known as the PoW technique. When multiple nodes nearly simultaneously discover the same nonce in a decentralized network, legitimate blocks may be generated at the same time. This may result in the formation of branches. Two competing forks, on the other hand, are unlikely to produce the nextblock at the same time. In the PoW protocol, a chain that becomes longer will be deemed genuine. Consider two forks created by validating blocks U4 and B4 at the same time. Miners continue to mine their blocks until a longer branch is discovered. Some Pow protocols have been created to minimize the loss while working with side apps. For example, Primecoin searches for unique prime number chains for use in mathematics. PoS is an alternative to Pow in terms of energy conservation. The PoS miners must provide proof of money ownership. People with more currencies would be less likely to be targeted by the network. The account balance was chosen incorrectly, since the strongest individual in the network is supposed to be the richest. As a consequence, various techniques for determining which block should be forged using the stake dimensions together have been suggested. Black Coin, in particular, forecasts randomness for the following generator. The formula compares the stake size to the lowest hash value.

Age-based selection is supported by Peercoin. In peercoin, the following block is more likely to be infected by older and bigger currencies. PoS saves more energy and is more powerful than PoW. Unfortunately, since mining expenses are so low, assaults may be the result. Most blockchains start with PoW and eventually move to PoS. For example, Ethereum is intending to transition from Ethash (Pow) to Casper (PoS). The PBFT method is used to replicate Byzantine defect tolerances. Because PBFT can tolerate up to 1/2 byzantine copies of harmful information, the Hyper Ledger Fabric PBFT algorithm is utilized. In the shape of a circle, a new block has been constructed. Each round, a primary is chosen based on a set of criteria. It is critical that the transaction be completed in the correct sequence.

The whole cycle may be broken down into three stages: preparation, preparation, and dedication. If two-thirds of all nodes vote in favor of a node, it advances to the next stage. As a result, every network node's knowledge is included in PBFT. A Stellar Consensus Protocol (SCP), such as PBFT, is often used for a Byzantine agreement. Through PBFT, the node must look for more nodes, and SCP requires participants to identify the communities of other participants on whom they may depend. On the basis of PBFT, the dBFT (delegated Byzantine tolerance for faults) was developed. Delegated Stakeholder Proof (dBFT) records transactions in several eligible nodes (DPOS).

PoS and DPOS vary in terms of democracy, with DPOS serving as a democratic representative. Stakeholders choose their leaders for block building and validation. The block may be examined and verified rapidly using somewhat lower nodes for network validation. People, on the other hand, do not have to consider the corrupt members since they may just opt out. The backbone is Bitshares' DPOS.

Ripple is a consensus method that employs trustworthy subnets across the network. Participating servers and money transfer consumers are the two kinds of network nodes. A unique node list exists for each application (UNL). For the server, UNL is crucial. If a transaction is to be put into the header, the server will check for UNL nodes so if the agreements reached 80%, the transaction will be packed into the leader. As long as the proportion of defective nodes in UNL is less than 20%, the header is correct for a node. The Byzantine consensus algorithm is the mint. In a circle, a new block is being created. This round, a proponent was selected to broadcast an unknown block. Its canister may be divided into three stages:

- *Prevote step:* The authenticator must determine whether or not to broadcast a preview of the proposed block.
- *Precommit step:* If more than  $2/3$  of the predictions for the proposed segment have been achieved, the node will broadcast a precommit. If the node receives more than  $2/3$  pre-commits, the commit procedure begins.

The node verifies the block and sends a commit in the third step. When  $2/3$  of the transfers have been received by the nodes, the block will be authorized. Nodes must obtain validators for their currencies in contrast to PBFT. If a validator is dishonest, they will be disciplined.

### G. Recent advancements and challenges

While blockchain has a lot of promise, it seems to be used to solve a lot of issues. They claim that Blockchain sustainability is spherical, with a steady increase in trade volume. usage, as well as current advancements in this area. With the growing number of trades on a blockchain, scalability becomes a problem. Because it must check whether or not the source of the transaction is unused, every node must record all transactions for blockchain authentication. Because of the initial limitation of block size and time period required to create a new block, the blockchain Bitcoin can now only process transactions per second, which does not meet the demand of performing millions of activities in real time. Because the blocks' capacity is so limited, many tiny transactions may be delayed because miners favor high transaction fees. The scalability issue in blockchain may be handled in a variety of ways, but they can be divided into two categories:

- *Blockchain stowage optimization:* As it becomes simpler for a node to execute a full copy of the ledger, Bruce suggested a new blockchain software that ignores (or excludes) the network's current transaction history. The balance of every non-empty address is kept in a data base the account tree. A lightweight customer may also address this issue. A new method called VerSum was suggested as another way to enable lightweight customers to exist. VerSum enables light consumers to provide large inputs with expensive

estimations. By comparing the data of several servers, it ensures that the findings are correct.

- A suggestion has been made to create Bitcoin-NG, which will reshape the blockchain. The primary concept behind Bitcoin-NG is to split conservative blocks into two parts: a key block for leadership contest as well as a micro block for stocking transactions. Epochs were created as a result of this protocol. In each era, miners must muddle to create a main block. When the main hunk is still being created, the node is in charge of producing microblocks. Bitcoin-NG has additionally extended a chain approach for microBlocks that has the heaviest (longest) weight. This changes the way blockchain works and resolves the link between information security and block size.

## II. DISCUSSION

The Bitcoin-underpinning blockchain technology has recently acquired a lot of momentum. Blockchain is an immutable decentralized transaction ledger. Financial services, reputation systems, and the Internet of Things (IoT) are among the areas where blockchain applications are gaining traction. Concerns with blockchain knowledge, like as security and scalability, have yet to be addressed. Bitcoin is unsuited for high-frequency trading since it can only handle 7 transactions per second. Larger blocks, on the other hand, mean greater storage and less network traffic. The purpose of this article is to provide an overview of blockchain technology. This article begins by providing an overview of blockchain technology and its primary purposes. Instead, the conventional blockchain consensus techniques are discussed in this article. In a number of methods, these approaches have been explored and contrasted. The article also discusses some of the difficulties and issues that may impede blockchain adoption, as well as some of the current solutions. In addition, there are suggestions for future paths. Blockchain contributions are becoming more frequent, and academics are intending to investigate blockchain-based applications in depth in the future.

## III. CONCLUSION

With its core characteristics of persistency, decentralization, auditability, and anonymity, Blockchain has the potential to revolutionize conventional industries. A blockchain is a distributed ledger in which all transactions are recorded in a block list. As additional blocks are added, the cable continues to grow. Asymmetric encryption and global consensus methods have been implemented for device protection and header compatibility. This paper provides an overview of blockchain technology. First, this article provides an overview of blockchain technology and its main functions. Instead, this article discusses the standard blockchain consensus methods. These techniques have been investigated and compared in a variety of ways. In addition, the article addresses the challenges and problems that may stymie blockchain adoption, as well as some of the existing solutions. There are also recommendations for future

directions. Blockchain contributions are becoming more common, and researchers are planning to do an extensive future study on blockchain-based applications.

### REFERENCES

- [1]. Frueh S. The Fourth Industrial Revolution Proceedings of a Workshop—in Brief MAKING VALUE FOR AMERICA. Natl Acad Sci Eng Med. 2017;
- [2]. Kokina J, Mancha R, Pachamanova D. Blockchain: Emergent industry adoption and implications for accounting. *J Emerg Technol Account*. 2017;
- [3]. Nowiński W, Kozma M. How can blockchain technology disrupt the existing business models? *Entrep Bus Econ Rev*. 2017;
- [4]. Casey M, Crane J, Gensler G, Johnson S, Narula N. The Impact of Blockchain Technology on Finance: A Catalyst for Change Centre for Economic Policy Research. *Geneva Reports on the World Economy*. 2018.
- [5]. Tinu NS. A Survey on Blockchain Technology-Taxonomy, Consensus Algorithms and Applications. *Int J Comput Sci Eng*. 2018;
- [6]. Sikorski JJ, Haughton J, Kraft M. Blockchain technology in the chemical industry: Machine-to-machine electricity market. *Appl Energy*. 2017;
- [7]. Finck M. Blockchains: Regulating the Unknown. *Ger Law J*. 2018;
- [8]. N.N. Blockchain Bicycle Carbon Trading Platform. NN. 2018;
- [9]. Newswire PR. Global Blockchain Technology Industry. NY-Reportlinker. 2018;
- [10]. Finck M. Law & the new Economy Blockchains: Regulating the Unknown. *Ger Law J*. 2018;